



Product Service

# Attestation of Conformity

No. N8A 076729 0114 Rev. 25

**Holder of Attestation:** **Seraphim Solar System Co., Ltd.**

No. 1-2, Hengyao Rd  
Henglin Zhen, Wujin District  
213101 Changzhou  
PEOPLE'S REPUBLIC OF CHINA

**Product:** **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**  
**Mono-crystalline Silicon Photovoltaic Module**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 704061801207-31

**Date,** 2024-11-18

( Zhulin Zhang )

Page 1 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



# Attestation of Conformity

No. N8A 076729 0114 Rev. 25

## Model(s):

1500 V DC Maximum System voltage, Fire Safety Class C Modules:

- SRP-xxx-6MA-HV (xxx=330-400, in steps of 5);
- SRP-xxx-6MB-HV (xxx=275-330, in steps of 5);
- SRP-xxx-E01A-HV (xxx=365-420, in steps of 5);
- SRP-xxx-E01B-HV (xxx=305-350, in steps of 5);
- SRP-xxx-BMA-HV (xxx=330-455 and xxx=525-560, in steps of 5);
- SRP-xxx-BMB-HV (xxx=275-380 and xxx=440-465 and xxx=590-610, in steps of 5);
- SRP-xxx-BMC-HV (xxx=305-380 and xxx=485-510 and xxx=650-675, in steps of 5);
- SRP-xxx-BMD-HV (xxx=390-420 and xxx=535-550, in steps of 5);
- SRP-xxx-BME-HV (xxx=475-490, in steps of 5);
- SRP-xxx-BMF-HV (xxx=415-430, in steps of 5);
- SRP-xxx-E6A-HV (xxx=410-435, in steps of 5);
- SRP-xxx-E6B-HV (xxx=350-370, in steps of 5);
- SRP-xxx-BMZ-HV (xxx=425-450 and xxx=565-605, in steps of 5);
- SRP-xxx-6MA-TB (xxx=330-400, in steps of 5);
- SRP-xxx-6MB-TB (xxx=275-330, in steps of 5);
- SRP-xxx-E01A-TB (xxx=365-420, in steps of 5);
- SRP-xxx-E01B-TB (xxx=305-350, in steps of 5);
- SRP-xxx-BMA-TB (xxx=330-455 and xxx=525-560, in steps of 5);
- SRP-xxx-BMB-TB (xxx=275-380 and xxx=440-465 and xxx=590-610, in steps of 5);
- SRP-xxx-BMC-TB (xxx=305-380 and xxx=485-510 and xxx=650-675, in steps of 5);
- SRP-xxx-BMD-TB (xxx=390-420 and xxx=535-550, in steps of 5);
- SRP-xxx-BME-TB (xxx=475-490, in steps of 5);
- SRP-xxx-BMF-TB (xxx=415-430, in steps of 5);
- SRP-xxx-E6A-TB (xxx=410-435, in steps of 5);
- SRP-xxx-E6B-TB (xxx=350-370, in steps of 5);
- SRP-xxx-BMZ-TB (xxx=425-450 and xxx=565-605, in steps of 5);
- SRP-xxx-TM72-HV (xxx=530-555, in steps of 5);
- SRP-xxx-TM68-HV (xxx=500-520, in steps of 5);
- SRP-xxx-TM64-HV (xxx=475-490, in steps of 5);
- SRP-xxx-TM60-HV (xxx=445-460, in steps of 5);
- SRP-xxx-TM56-HV (xxx=415-430, in steps of 5);
- SRP-xxx-TM52-HV (xxx=385-400, in steps of 5);
- SRP-xxx-TM48-HV (xxx=355-370, in steps of 5);
- SRP-xxx-BTA-HV (xxx=550-590, in steps of 5);
- SRP-xxx-BTB-HV (xxx=460-490, in steps of 5);
- SRP-xxx-BTC-HV (xxx=505-540, in steps of 5);
- SRP-xxx-BTD-HV (xxx=415-440, in steps of 5);
- SRP-xxx-BTZ-HV (xxx=595-625, in steps of 5);

1000 V DC Maximum System voltage, Fire Safety Class C Modules:

- SRP-xxx-6MA (xxx=330-400, in steps of 5);
- SRP-xxx-6MB (xxx=275-330, in steps of 5);
- SRP-xxx-E01A (xxx=365-420, in steps of 5);
- SRP-xxx-E01B (xxx=305-350, in steps of 5);
- SRP-xxx-BMA (xxx=330-455 and xxx=525-560, in steps of 5);
- SRP-xxx-BMB (xxx=275-380 and xxx=440-465 and xxx=590-610, in steps of 5);
- SRP-xxx-BMC (xxx=305-380 and xxx=485-510 and xxx=650-675, in steps of 5);
- SRP-xxx-BMD (xxx=390-420 and xxx=535-550, in steps of 5);
- SRP-xxx-BME (xxx=475-490, in steps of 5);
- SRP-xxx-BMF (xxx=415-430, in steps of 5);
- SRP-xxx-E6A (xxx=410-435, in steps of 5);
- SRP-xxx-E6B (xxx=350-370, in steps of 5);
- SRP-xxx-BMZ (xxx=425-450 and xxx=565-605, in steps of 5);

1500 V DC Maximum System voltage, Fire Safety Class A Modules:

Page 2 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



# Attestation of Conformity

No. N8A 076729 0114 Rev. 25

SRP-xxx-6MA-BG (xxx=350-395, in steps of 5);  
 SRP-xxx-6MB-BG (xxx=295-325, in steps of 5);  
 SRP-xxx-6MA-DG (xxx=350-395, in steps of 5);  
 SRP-xxx-6MB-DG (xxx=295-325, in steps of 5);  
 SRP-xxx-BMA-BG (xxx=330-455 and xxx=525-560, in steps of 5);  
 SRP-xxx-BMB-BG  
 (xxx=290-380 and xxx=440-465 and xxx=590-610, in steps of 5);  
 SRP-xxx-BMC-BG  
 (xxx=320-375 and xxx=485-510 and xxx=650-675, in steps of 5);  
 SRP-xxx-BMD-BG (xxx=395-420 and xxx=535-545, in steps of 5);  
 SRP-xxx-BME-BG (xxx=475-490, in steps of 5);  
 SRP-xxx-BMF-BG (xxx=415-430, in steps of 5);  
 SRP-xxx-BMA-DG (xxx=350-425, in steps of 5);  
 SRP-xxx-BMB-DG (xxx=290-350, in steps of 5);  
 SRP-xxx-BMC-DG (xxx=320-350, in steps of 5);  
 SRP-xxx-BMZ-BG (xxx=425-450 and xxx=565-605, in steps of 5);  
 SRP-xxx-TM72-BG (xxx=530-555, in steps of 5);  
 SRP-xxx-TM68-BG (xxx=500-520, in steps of 5);  
 SRP-xxx-TM64-BG (xxx=475-490, in steps of 5);  
 SRP-xxx-TM60-BG (xxx=445-460, in steps of 5);  
 SRP-xxx-TM56-BG (xxx=415-430, in steps of 5);  
 SRP-xxx-TM52-BG (xxx=385-400, in steps of 5);  
 SRP-xxx-TM48-BG (xxx=355-370, in steps of 5);  
 SRP-xxx-BTA-BG (xxx=550-590, in steps of 5);  
 SRP-xxx-BTB-BG (xxx=460-490, in steps of 5);  
 SRP-xxx-BTC-BG (xxx=505-540, in steps of 5);  
 SRP-xxx-BTD-BG (xxx=415-440, in steps of 5);  
 SRP-xxx-BTZ-BG (xxx=595-625, in steps of 5).

Imbricated photovoltaic modules  
 600 V DC Maximum System voltage:  
 SRF-ExxxA (xxx=360 and 370-380, in steps of 5);  
 1500 V DC Maximum System voltage:  
 SRF-ExxxA (xxx=530-560, in steps of 5).  
 xxx is standing for rated output power at STC.

## Parameters:

Safety Class:	Class II
Max. System Voltage:	1000V DC or 1500V DC
Test Laboratory:	Changzhou HuaYang Inspection and Testing Technology Co., Ltd No.8 Lanxiang Road Wujin Economic Development Zone Changzhou, Jiangsu, China.
Construction:	Framed or Frameless, with Junction box, cable and connector.
Fire Safety Class:	Class C or Class A according to UL790

## Tested according to:

EN IEC 61730-1:2018  
 EN IEC 61730-1:2018/AC:2018-06  
 EN IEC 61730-2:2018  
 EN IEC 61730-2:2018/AC:2018-06

Page 3 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.